

Solenoid operated poppet valve

Installation in pipes


- ◆ 2/2-way
- ◆ normally open and normally closed
- ◆ threaded connection 1/4"
- ◆ $Q_{\max} = 15 \text{ l/min}$
- ◆ $p_{\max} = 350 \text{ bar}$

DESCRIPTION


Direct operated 2/2-way solenoid poppet valve for installation in pipes. By means of the pressure tight switching solenoid, the poppet valve spool is opened or closed acting against the spring. Due to the poppet spool construction with pressure compensation on both sides, the flow through the valve is possible in both directions. The seat spool guide is sealed by means of an O-ring. The metallic sealing seat closes the valve virtually leak free.

SYMBOL

G.22041



NG4




APPLICATION

Poppet valves are used where tight closing functions of the valve are essential like leakage-free load holding, clamping or gripping.

TYPE CODE

G.22040



G S 22 04 - - #

Threaded connection

Solenoid, Super

2 way (connections)

2 switching positions

Nominal size 4

Normally closed

10

Nominal voltage U_N

12 VDC
24 VDC

G12
G24

115 VAC
230 VAC

R115
R230

Sealing material

NBR

FKM (Viton)

D1

Design index (subject to change)

1.11-2820

COMMISSIONING

Attention! When commissioning, the valve must be vented under pressure (max. 2 rotations of screw E).



ACTUATION

Actuation

Switching solenoid, wet pin push type,
pressure tight

Execution

SIS35V (Data sheet 1.1-110)

Connection

Connector socket DIN EN 175301 – 803

GENERAL SPECIFICATIONS

Designation	2/2-way poppet valve
Construction	Direct operated
Mounting	Installation in pipes
Nominal size	NG4
Connection	Threaded connection G1/4"
Actuation	Switching solenoid
Ambient temperature	-25...+70 °C (NBR) -20...+70 °C (FKM)
Weight	≤ 1,2 kg
MTTFd	150 years

ELECTRICAL SPECIFICATIONS

Protection class	IP65
Relative duty factor	100 % DF
Switching frequency	15'000 / h
Service life time	10 ⁷ (number of switching cycles, theoretically)
Voltage tolerance	± 10 % with regard to nominal voltage
Standard nominal voltage	12 VDC, 24VDC, 115 VAC, 230 VAC AC = 50 to 60 Hz, rectifier integrated in the connector socket

Note! Other electrical specifications see data sheet 1.1-110



SEALING MATERIAL

NBR or FKM (Viton) as standard, choice in the type code

HYDRAULIC SPECIFICATIONS

Working pressure	$p_{max} = 350$ bar
Maximum volume flow	$Q_{max} = 15$ l/min, see characteristic
Volume flow direction	Any (see characteristic)
Leakage oil	Poppet type, max. 0,05 ml / min (approx. 1 drop / min) at 30 cSt
Fluid	Mineral oil, other fluid on request
Viscosity range	12 mm ² /s...320 mm ² /s
Temperature range fluid	-25...+70 °C (NBR) -20...+70 °C (FKM)
Contamination efficiency	Class 20 / 18 / 14
Filtration	Required filtration grade $\beta_{10...16} \geq 75$, see data sheet 1.0-50

STANDARDS



Solenoids	DIN VDE 0580
Connection execution D	DIN EN 175301 – 803
Protection class	EN 60 529
Contamination efficiency	ISO 4406

SURFACE TREATMENT

- ◆ The valve body, the solenoid, the cover and the socket head screws are zinc coated

PERFORMANCE SPECIFICATIONS

Oil viscosity $\nu = 30$ mm²/s




Type	Flow direction	
	P → A	A → P
GS2204	1	2

VALVES INSTALLED

Zentrales Funktionselement ist die Sitzventilpatrone NG4, Datenblatt 1.11-2020.


DIMENSIONS

G.22041



E = Air bleed screw

G.22040



PARTS LIST

Position	Article	Description
10	260.5...	Solenoid SIS35V
20	239.2033	Screw plug HB0 (incl. seal)
30	219.2001	Mating connector DIN EN 175301-803 grey
35	219.2002	Mating connector DIN EN 175301-803 black
40	056.4201	Cover
50	246.1161	Socket head screw M4 x 60 DIN 912
60	246.1113	Socket head screw M4 x 12 DIN 912

MANUAL OVERRIDE

Screw plug (HB0), no actuation possible
 Optionally: See data sheet 1.1-300 and 1.1-311.

INSTALLATION NOTES

Mounting position: Any, preferably horizontal

ACCESSORIES

Technical explanations	Data sheet 1.0-100
Filtration	Data sheet 1.0-50
Relative duty factor	Data sheet 1.1-430