Proportional pressure reducing cartridge

- pilot operated
- Q_{max} = 20 l/min
- p_{max} = 350 bar
- $p_{N\ red\ max}$ = 315 bar

M18 x 1,5
Wandfluh standard



DESCRIPTION

Pilot operated proportional pressure reducing valve in screw-in cartridge construction for cavity according to Wandfluh standard. Proportionally to the solenoid current, the solenoid force and the pressure in port A (1) rise. The valve functions practically independently of the pressure in port P (2). Pressure increase in the consumer port A (1) to above the adjusted value, e.g. through an active consumer, is avoided by discharging excess oil to the tank T (3). With the solenoid deenergised, the oil flows freely from port P (2) to consumer port A (1). For the control, Wandfluh proportional amplifiers are available (see register 1.13).

APPLICATION

The electrical remote control in conjunction with process controls allows economical solutions with repeatable processes. The screw-in cartridge is perfectly suitable for installation in control blocks and is installed in sandwich- (vertical stacked systems) and in flange plates (corresponding data sheets in this register). For machining the cartridge cavity in steel and aluminum blocks, cavity tools are available (hire or purchase). Please refer to the data sheets in register 2.13.

SYMBOL



ACTUATION

Actuation	Proportional solenoid, wet pin push type, pressure tight
Execution	PI29V (data sheet 1.1-90)
Connection	Connector socket DIN EN 175301 – 803

TYPE CODE

M V P PM18 - [ ] - [ ] - [ ] # [ ]

Pressure reducing valve				
Pilot operated				
Proportional				
Screw-in cartridge M18 x 1,5				
Nominal pressure range $p_{N\ red}$	20 bar	20	200 bar	200
	100 bar	100	315 bar	315
Nominal voltage U_N	12 VDC	G12		
	24 VDC	G24		
Sealing material	NBR			
	FKM (Viton)	D1		
Design index (subject to change)				

2.3-610

GENERAL SPECIFICATIONS

Designation	Proportional pressure reducing valve
Construction	Pilot operated
Mounting	Screw-in cartridge construction
Nominal size	M18 x 1,5 according to Wandfluh standard
Actuation	Proportional solenoid
Ambient temperature	-25…+70 °C
Weight	0,40 kg
MTTFd	150 years

HYDRAULIC SPECIFICATIONS

Working pressure	p_{max} = 350 bar
Nominal pressure range	$P_{N\ red}$ = 20 bar, 100 bar, 200 bar, 315 bar
Volume flow range	Q = 0…20 l/miin
Leakage oil	See characteristics
Hysteresis	≤ 4 % at optimal dither signal
Repeatability	≤ 1 % at optimal dither signal
Fluid	Mineral oil, other fluid on request
Viscosity range	12 mm²/s…320 mm²/s
Temperature range fluid	-25…+70 °C (NBR) -20…+70 °C (FKM)
Contamination efficiency	Class 18 / 16 / 13
Filtration	Required filtration grade ß 6…10 ≥ 75, see data sheet 1.0-50

ELECTRICAL SPECIFICATIONS

Protection class	IP65
Relative duty factor	100 % DF
Service life time	10^7 (number of switching cycles, theoretically)
Voltage tolerance	± 10 % with regard to nominal voltage
Standard nominal voltage	12 VDC, 24 VDC
Limiting current at 50 °C	I_G = 1080 mA (12 VDC) I_G = 540 mA (24 VDC)

Note! Other electrical specifications see data sheet 1.1-90

PERFORMANCE SPECIFICATIONS

Oil viscosity υ = 30 mm²/s

p_{red} = f (Q) **Pressure volume flow characteristics**
Maximal adjustable pressure



p_{red} = f (Q) **Pressure volume flow characteristics**
Minimal adjustable pressure
*Consumer resistance depending on the system



p_{red} = f (n) **Pressure adjustment characteristics**
Measured at Q = 0 l/min (static)



Q_L = f (p) **Leakage volume flow characteristic**
A (1) → T (3)



DIMENSIONS



HYDRAULIC CONNECTION

Cavity drawing according to Wandfluh standard



Note! For detailed cavity drawing and cavity tools see data sheet 2.13-1020

PARTS LIST

Position	Article	Description
10	256.2418	Proportional solenoid PI29V-G12
	256.2453	Proportional solenoid PI29V-G24
15	253.8000	Manual override HB4,5
30	219.2002	Electric plug B (black)
40	246.0151	Socket head screw M3 x 50 DIN 912
	251.1004	Seal kit MVPPM18
	251.3117	Seal kit MVPPM18-D1
	251.3118	Seal kit MVPPM18-D2

Seal kit consisting of:

18	O-ring	ID 12,42 x 1,78
50	O-ring	ID 15,60 x 1,78
60	O-ring	ID 11,11 x 1,78
70	Back. ring	PTFE rd 12,1 x 15 x 1,4
80	O-ring	ID 9,25 x 1,78
90	Back. ring	PTFE rd 10,6 x 13,5 x 1,4

ACCESSORIES

Proportional amplifier	Register 1.13
Flange body / sandwich plate NG3-Mini	Data sheet 2.3-800
Threaded body	Data sheet 2.9-210
Technical explanations	Data sheet 1.0-100
Filtration	Data sheet 1.0-50

MANUAL OVERRIDE

Standard: HB4,5

Optionally: Screw plug (HBO), no actuation possible.

Attention! If the manual override is actuated, the nominal pressure level may be exceeded.

SURFACE TREATMENT

- All external parts of the cartridge as well the solenoid coil are zinc-nickel coated

SEALING MATERIAL

NBR or FKM (Viton) as standard, choice in the type code

STANDARDS

Cartridge cavity	Wandfluh standard
Solenoids	DIN VDE 0580
Connection execution D	DIN EN 175301 – 803
Protection class	EN 60 529
Contamination efficiency	ISO 4406

INSTALLATION NOTES

Mounting type	Screw-in cartridge M18 x 1,5
Mounting position	Any, preferably horizontal
Tightening torque	M_D = 40 Nm Screw-in cartridge M_D = 1,2 Nm solenoid screws