

Pressure switch hex 27

Accessories and applications



- Socket device IP65 or rubber capped IP54 for increased protection
- Easy installation with mountable socket device
- Thread adapters for special threads

hex 27 accessories



Rubber protective cap

with two cable feeds for 1.7 to 2.3 mm diameter cable

When rubber cap attached
IP54

Suitable for voltages up to 42 V



Socket device

Threaded connection Pg9 (Tightening range 6 - 9 mm)

When attached to socket device
IP65

Suitable for voltages up to 250 V




Socket device with indicator light

According to DIN EN 175301- 803-A (DIN 43650)

Threaded connection Pg9 (Tightening range 6 - 9 mm)

When attached to socket device
IP65

Suitable for 24 V or 250 V



Thread adapter for special threads

from G1/4-DIN3852-E to R1/4 acc. to DIN 2999

including FKM seals

0170 / 0171



0180 / 0181

(Up to max 42 V)



0183

(Up to max 42 V)



0184 / 0185

24 V or 250 V (upon request) see also page 33



0190 / 0191



0194 / 0195

(24 V on request) also see page 35



0186 / 0187

(Up to max 42 V)



0196 / 0197



Order number:

1-1-70-621-007

1-1-80-652-002

24 VDC: 1-1-84-652-011

1-1-00-420-009

250 VAC: 1-1-84-652-010